



**WEIGHT:** 1500 lbs (not including accessories)  
**POWER CONSUMPTION:** Sealing Only Models: 3Kw, VG Models: 5Kw. (may vary depending on options included)  
**VOLTAGE:** 208/220/480V 3 phase 60Hz  
**DRIVEN:** "Servo" Brushless Motor  
**AIR REQUIREMENT:** 90psi (6 bar)  
**AIR CONSUMPTION:** 0.5 to 1 (standard) cfm  
**MAX OD FOR FILM:** 11.8" (300 mm.) and/or 66 lbs. (30kg)  
**SPEED / OUTPUT:** 10-12+ cycles w/MAP, 15+ sealing only (application dependent)  
**MAX SEALING AREA:** 400x265x120h



**WEIGHT:** 1800 lbs (not including accessories)  
**POWER CONSUMPTION:** Sealing Only Models: 5Kw, VG Models: 7Kw. (may vary depending on options included)  
**VOLTAGE:** 208/220/480V 3 phase 60Hz  
**DRIVEN:** "Servo" Brushless Motor  
**AIR REQUIREMENT:** 90psi (6 bar)  
**AIR CONSUMPTION:** 0.5 to 1 (standard) cfm  
**MAX OD FOR FILM:** 11.8" (300 mm.) and/or 66 lbs. (30kg)  
**SPEED / OUTPUT:** 10-12 cycles w/MAP, 12-15 sealing only (application dependent)  
**MAX SEALING AREA:** 650x350x120h



**WEIGHT:** 2200 lbs (not including accessories)  
**POWER CONSUMPTION:** Sealing Only Models: 7Kw, VG Models: 9Kw. (may vary depending on options included)  
**VOLTAGE:** 208/220/480V 3 phase 60Hz  
**DRIVEN:** "Servo" Brushless Motor  
**AIR REQUIREMENT:** 90psi (6 bar)  
**AIR CONSUMPTION:** 0.5 to 1 (standard) cfm  
**MAX OD FOR FILM:** 11.8" (300 mm.) and/or 66 lbs. (30kg)  
**SPEED / OUTPUT:** 10-12 cycles w/MAP, 15 sealing only (application dependent)  
**MAX SEALING AREA:** 850x350x120h

