Foodpack Speedy PN18





WEIGHT: 1450 lbs. (not including accessories)
POWER CONSUMPTION: Sealing Only Models: 3.5Kw, VG Models: 5Kw. (may vary depending on options included)
VOLTAGE: 208/220V 3 phase 60Hz

DRIVEN: Pneumatic

AIR REQUIREMENT: 90psi (6 bar) AIR CONSUMPTION: 3 (standard) cfm

MAX OD FOR FILM:11.8" (300 mm.) and/or 53 lbs. max

SPEED / OUTPUT: 10 cycles w/MAP, 15 sealing only (application dependent)

MAX SEALING AREA: 380x270x135mm



WEIGHT: 1800 lbs. (not including accessories)
POWER CONSUMPTION: Sealing Only Models: 5.5Kw, VG Models: 7Kw. (may vary depending on options included)
VOLTAGE: 208/220V 3 phase 60Hz

DRIVEN: "Servo" Brushless Motor AIR REQUIREMENT: 90psi (6 bar)

AIR CONSUMPTION: 0.5 to 1 (standard) cfm MAX OD FOR FILM: 11.8" (300 mm.) and/or 66 lbs. max

SPEED / OUTPUT: Up to 10 cycles w/MAP, up to 15 sealing only (application dependent)

MAX SEALING AREA: 500x270x135mm



WEIGHT: 2550 lbs. (not including accessories)
POWER CONSUMPTION: Sealing Only Models: 13Kw, VG Models: 15Kw. (may vary depending on options included)

VOLTAGE: 208/220V 3 phase 60Hz DRIVEN: "Servo" Brushless Motor
AIR REQUIREMENT: 90psi (6 bar)
AIR CONSUMPTION: 0.5 to 1 (standard) cfm

MAX OD FOR FILM: 11.8" (300 mm.) and/or 66 lbs. max

SPEED / OUTPUT: Up tp 10 cycles w/MAP, up to 15 sealing only (application dependent)

MAX SEALING AREA: 640x330x135mm







